

Technical data sheet

PVC control cables · shielded

LÜTZE SILFLEX® N (C) PVC MULTINORM With approvals for Europe and North America



Identification

Type SI N(C)PVC(2×0,5)MN
Part No. [109800](#)

Product version

Datasheet version 00

Use/Application/Properties

- Application
- Machine and device construction, transport and conveyor technology, heating and climate technology
 - In dry, damp and wet rooms
 - As a monitoring, measurement and control cable for industrial applications
 - For flexible applications without compulsory guide
 - Anywhere where electrical interference fields can influence the signal transmission
- Properties
- UL recognized for use in North America
 - Easy stripping and fast installation
 - High flexibility for complex installation distances and small bending radii
 - Improved oil resistance due to specifically developed PVC jacket
 - Resistance to many oils, coolants and solvents
 - Hydrolysis-resistant, microbe-resistant, and rot-resistant
 - Silicone free

Construction

Description SILFLEX® N (C) PVC MULTINORM
Number of conductors/cross-section (2×0.5)
Number of conductors 2
Cross-section, metric 0.5 mm²
Jacket material Special PVC
Jacket color grey similar to RAL 7001
Outer Ø 5.6 mm

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk

Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) • Bruckwiesenstraße 17-19 • D-71384 Weinstadt
Tel. +49 (0)7151 6053-0 • Fax +49 (0)7151 6053-277(-288)
www.luetze.de • info@luetze.de

29.03.2023 • Subject to technical modification

Part No. [109800](#) • Datasheet version: 00

page 1 of 3



SYSTEMATIC TECHNOLOGY

Technical data sheet

PVC control cables · shielded

Weight	4.8 kg/100 m
Cu-Index	2.37 kg/100 m

Construction Element 1

Element construction	(2×0.5)
Conductor	CU-wire bare
Conductor category	IEC 60228, Class 5 Finely stranded DIN VDE 0295 Class 5
Conductor marking	black · with white number print
Conductor insulation	Special PVC

Overall construction

Overall stranding	layered construction
Overall wrapping	Non-woven material
Overall shield	Braid shield tinned copper wires optical cover approx. 85 %
Jacket characteristics	Flame-retardant Oil resistant coolant-resistant solvent-resistant hydrolysis-resistant microbe resistant Silicone-free

Technical data

Rated voltage U_0/U	300/500 V
Rated voltage UL	600 V
Test voltage type	AC 6000 V
Temperature according to UL	90 °C
Temperature range UL moving	-5 °C ... +90 °C
Temperature range UL fixed	-40 °C ... +90 °C
Temperature range VDE moving	-5 °C ... +70 °C
Temperature range VDE fixed	-25 °C ... +70 °C
Minimum bending radius moving	15×D
Minimum bending radius fixed	6×D

Technical Data Element 1

Element construction	(2×0.5)
Insulation resistance at 20 °C	≥20 MΩ×km
Operating capacitance wire-wire	approx.134 pF/m
Operating capacitance wire-shield	approx.142 pF/m

Technical data sheet

PVC control cables · shielded

Certifications/Standards

Certifications	cURus AWM I/II A/B FT1 VDE
UL style	AWM 2587
Conformity	CE RoHS REACH
Burning behavior according to	IEC 60332-1 IEC 60332-3-24 UL FT1 UL VW-1
Oil resistant according to	Oil Res II

General

Note	CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU
------	--