


## Technical data sheet

PUR electronic cables · C-track compatible · Shielded

**LÜTZE SUPERFLEX® TRONIC (C) PUR TP**  
Shielded electronic cable UL recognized, paired  
For highest requirements



### Identification

Type SU TR (C) PUR TP (3×2×0,34)  
Part No. [117181](#)

### Product version

Datasheet version 00

### Use/Application/Properties

- Application
- C-track as well as everywhere where signals are transmitted to continuously moving system or machine parts
  - Machine and device construction, transport and conveyor technology, heating and climate technology
  - In dry and damp rooms
  - As monitoring, measurement and control cable for continuous bending loads
  - Especially for industrial environments with high EMI potential in machine, plant and device construction
- Properties
- High protection against electromagnetic interferences (EMI)
  - High crosstalk attenuation through paired stranding
  - Braided shield optimised for continuous flexing use
  - Low capacitance, very good electrical properties
  - Flame-retardant, self-extinguishing
  - Halogen-free, no corrosive gases
  - Very good alternating bending strength
  - Low adhesion, abrasion-resistant, nick-resistant, tear-resistant
  - Hydrolysis-resistant, microbe-resistant, and rot-resistant
  - Industrial and salt water resistant
  - Excellent coolant and lubricant resistance
  - Largely resistant to oils, greases, alcohol-free benzines and kerosene
  - Silicone free

### Construction

Description SUPERFLEX® TRONIC (C) PUR TP

#### United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington · GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 · Fax +44 (0)1827 31333-2  
www.lutze.com · sales.gb@lutze.co.uk

#### Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) · Bruckwiesenstraße 17-19 · D-71384 Weinstadt  
Tel. +49 (0)7151 6053-0 · Fax +49 (0)7151 6053-277(-288)  
www.luetze.de · info@luetze.de

14.04.2023 · Subject to technical modification

Part No. [117181](#) · Datasheet version: 00

page 1 of 3

## Technical data sheet

PUR electronic cables · C-track compatible · Shielded

---

Number of conductors/cross-section	(3×2×0.34)
Number of conductors	6
Cross-section, metric	0.34 mm <sup>2</sup>
Cross-section AWG	AWG 22
Jacket material	PUR
Jacket color	grey similar to RAL 7001
Outer Ø	6.8 mm
Outer Ø	0.268 inch
Surface	adhesion-free, matte
Weight	5.8 kg/100 m
Weight	39 Lbs/Mft
Cu-Index	3.4 kg/100 m
Cu-Index	23 Lbs/Mft

---

### Construction Element 1

---

Element construction	(3×2×0.34)
Conductor	CU-wire bare
Conductor category	IEC 60228, Class 6 Superfinely stranded DIN VDE 0295 Class 6
Conductor marking	Color coded
Conductor marking standard	DIN 47100
Conductor insulation	Special TPE

---

### Overall construction

---

Overall stranding	stranded pairs layer pitch optimised conductors twisted without mechanical stress
Overall wrapping	Non-woven material
Overall shield	Braid shield tinned copper wires optical cover approx. 85 %
Jacket characteristics	Flame-retardant self-extinguishing Halogen free Oil resistant grease-resistant petrol-resistant (alcohol-free) kerosene-resistant Silicone-free

---

### Technical data

---

Rated voltage	300 V
Test voltage type	AC 1500 V
Temperature according to UL	80 °C
Temperature range moving	-25 °C ... +80 °C
Temperature range fixed	-40 °C ... +80 °C

---

## Technical data sheet

PUR electronic cables · C-track compatible · Shielded

---

Minimum bending radius moving	12×D
Minimum bending radius fixed	6×D
Bending cycles	≥5 Mio
Travel distance	≤20 m
Speed	≤4
Acceleration	≤5

---

### Technical Data Element 1

---

Element construction	(3×2×0.34)
Insulation resistance at 20 °C	≥1000 MΩ×km

---

### Certifications/Standards

---

Certifications	cURus
UL style	AWM 20549
Conformity	CE RoHS REACH TSCA
Burning behavior according to	IEC 60332-2-2 DIN EN 60332-2-2 UL 1581 UL Horizontal Flame Test UL FT2
Oil resistant according to	DIN EN 50363-10-2
Halogen free according to	IEC 60754-1 DIN EN 60754-1
UV-resistant according to	UL 1581/2556-300h

---

### General

---

Note	CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU
------	--